Please amend the claims as follows:

Claim 1 (Currently Amended): An organic electroluminescence display element

comprising a first conductive layer, a second conductive layer opposed to the first conductive

layer, a driving circuit connecting terminal connected electrically to the first conductive layer

via a supplementary wire and an organic electroluminescence layer disposed between the first

conductive layer and the second conductive layer, wherein the supplementary wire has at

least one surface layer containing Mo or a Mo alloy, and a number of supplementary wires is

at least 30, and the supplementary wires are configured to carry at least 50 mA of current.

Claim 2 (Original): The organic electroluminescence display element according to

claim 1, wherein the first conductive layer is connected to the layer containing Mo or a Mo

alloy.

Claim 3 (Original): The organic electroluminescence display element according to

claim 1, wherein the second conductive layer is made of ITO.

Claim 4 (Original): The organic electroluminescence display element according to

claim 1, wherein the supplementary wire has a layer made of Al, an Al alloy, Ag or an Ag

alloy.

Claim 5 (Original): The organic electroluminescence display element according to

claim 1, wherein the first conductive layer is connected to an etched surface of the layer

containing Mo or a Mo alloy.

2

Claim 6 (Previously Presented): The organic electroluminescence display element according to claim 1, wherein a portion of the first conductive layer connected to the layer containing Mo or a Mo alloy is defined by an insulation film.

Claim 7 (Original): The organic electroluminescence display element according to claim 1, wherein the Mo alloy contains Nb.

Claim 8 (Previously Presented): The organic electroluminescence display element according to claim 7, wherein a content of Nb in the Mo alloy is 5 to 20 atomic %.

Claim 9 (Canceled).

Claim 10 (Previously Presented): The organic electroluminescence display element according to claim 1, wherein a portion of the first conductive layer connected to the supplementary wire contains Al or an Al alloy.

Claim 11 (Previously Presented): An organic electroluminescence display element comprising a first conductive layer, a second conductive layer opposed to the first conductive layer, a driving circuit connecting terminal connected electrically to the first conductive layer via a supplementary wire and an organic electroluminescence layer disposed between the first conductive layer and the second conductive layer, wherein the supplementary wire comprises at least 3 layers including a layer containing Mo or a Mo alloy as a surface layer and a layer containing Al or an Al alloy formed below the surface layer, and a number of supplementary wires is at least 30.

Claim 12 (Original): An organic electroluminescence display device comprising the organic electroluminescence display element described in claim 1 and a driving circuit for driving the organic electroluminescence display element.

Claim 13 (Canceled).

Claim 14 (New): The organic electroluminescence display element according to claim 11, wherein the first conductive layer is connected to the layer containing Mo or a Mo alloy.

Claim 15 (New): The organic electroluminescence display element according to claim 11, wherein the second conductive layer is made of ITO.

Claim 16 (New): The organic electroluminescence display element according to claim 11, wherein the supplementary wire has a layer made of Al, an Al alloy, Ag or an Ag alloy.

Claim 17 (New): The organic electroluminescence display element according to claim 11, wherein the first conductive layer is connected to an etched surface of the layer containing Mo or a Mo alloy.

Claim 18 (New): The organic electroluminescence display element according to claim 11, wherein a portion of the first conductive layer connected to the layer containing Mo or a Mo alloy is defined by an insulation film.

Claim 19 (New): The organic electroluminescence display element according to claim 11, wherein the Mo alloy contains Nb.

Application No. 10/828,416 Reply to Office Action of June 24, 2005

Claim 20 (New): The organic electroluminescence display element according to claim 19, wherein a content of Nb in the Mo alloy is 5 to 20 atomic %.

Claim 21 (New): The organic electroluminescence display element according to claim 11, wherein a portion of the first conductive layer connected to the supplementary wire contains Al or an Al alloy.

Claim 22 (New): An organic electroluminescence display device comprising the organic electroluminescence display element described in claim 11 and a driving circuit for driving the organic electroluminescence display element.